

9-Port Fast Ethernet Desktop PoE Switch

SF1009P



PoE



Plug & Play



Energy-Saving

Specifications

General

- Standards: IEEE 802.3、IEEE 802.3u、IEEE 802.3x、IEEE 802.3af、IEEE 802.3at
- Protocol: CSMA/CD
- Data Rate:
 - Ethernet: 10Mbps (Half Duplex)/20Mbps (Full Duplex)
 - Fast Ethernet: 100Mbps (Half Duplex)/200Mbps (Full Duplex)
- Transmission Method: Store-and-Forward
- Port Features:
 - Support IEEE802.3x flow control (half/full duplex)
 - Implemented via the VLAN ON/OFF switch on the front panel
 - VLAN ON: Ports 1-8 are isolated, but they can communicate with port 9
 - VLAN OFF: Ports 1-9 can intercommunicate with each other.

Hardware

- LED Indicators: Link/Act, PoE, Power, PoE-MAX
- MAC Address Table: 4K entries per device
- Power Supply: DC 48V 2.5A
 - Power Consumption: <120W
 - Maximum PoE Output Power: 115W
- Power Module: PoE 802.3af(15.4W)/802.3at(30W)
- Dimensions (W×D×H): 220mm x 94mm x 28mm

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Relative Humidity: 10%~90%, non-condensing
- Storage Humidity: 5%~90%, non-condensing

Package Contents

- 1 x 9-Port Desktop PoE Switch
- 1 x Power Adapter
- 1 x User Manual