

AC1200 WiFi Extender

RE721-V2



 Intelligent Signal Indicator

 Ethernet Port

 WPS

Specifications

General

- Wireless Standards: IEEE802.11a/n/ac,5GHz, IEEE802.11b/g/n,2.4GHz
- Signal Rate: 5GHz:Up to 867Mbps, 2.4GHz:Up to 300Mbps
- Operation Frequency: 2.4GHz and 5GHz
- Reception Sensitivity:
5GHz
11a 6Mbps: -82dBm, 11a 54Mbps: -65dBm
11ac HT20: -54dBm, 11ac HT40: -59dBm, 11ac HT80: -53dBm,
11n HT20: -62dBm, 11n HT40: -59dBm
2.4GHz
11g 54M: -69dBm
11n HT20: -67dBm, 11n HT40: -64dBm
- Wireless Security: WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption

Hardware

- Interfaces: 1 x 10/100Mbps LAN Port
- Buttons: WPS Button, Reset Button
- Power Supply: Plug-in
- Antenna: 2 x 3dBi external dual band antennas
- Dimensions (W X D X H): 102*70*39 mm

Software Features

- DHCP: Server, Client, DHCP Client List
- System management:
Firmware Upgrade
Reset Default
Reboot
User/Password
System Log
- Internet Protocol: IPv4, IPv6

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Relative Humidity: 10%~90%, non-condensing
- Storage Humidity: 5%~90%, non-condensing

Package Contents

- 1 x WiFi Extender RE721
- 1 x Quick Installation Guide

Certifications

- CE, RoHS